

Reference guide

# Empty chromatography columns for lab scale





| Column name   | Empty PD gravity-flow column  | C column                                       | Tricorn™ column  | XK column  | HiScale™ column   |
|---|---|--|--|--|---|
| <b>Main features</b>                                      | Plastic columns for operation using gravity flow  | Economical columns for low-pressure operation  | A high-pressure stable column with dimensions that are suitable for small-scale purification | A well-established column suitable for many different purification needs | Facilitated column packing with axial compression capabilities and column measurement scale |
| <b>Max. operating pressure</b>                            | Not applicable  | 1 bar*   | 50/100 bar depending on size of column*  | 3/5 bar depending on size of column*                                     | 20 bar*   |
| <b>Max. bed volume of the largest column in the range</b> | 13 mL   | 520 mL   | 50 mL  | 1860 mL  | 785 mL  |
| <b>For use with</b>                                       | Gravity flow  | Stand-alone pump or chromatography system      | Chromatography system  | Stand-alone pump or chromatography system                                | Chromatography system   |
| <b>Number of adapters supplied with the column</b>        | Not applicable  | Ordered separately                             | 1 adapter included   | 1 adapter included   | 2 adapters included   |
| <b>Available as prepacked column</b>                      | Yes<br>(PD-10 Columns, GraviTrap™)  | No   | Yes<br>(Tricorn GL)  | Yes<br>(HiLoad™)   | Yes<br>(On-demand packing <sup>†</sup> )  |
| <b>Base matrix compatibility</b>                          |   |  |  |  |   |
| <b>Affinity chromatography</b>                            | Sepharose™ 4B, 6B, CL-4B, CL-6B<br>Sepharose High Performance (HP)<br>Sepharose 4 Fast Flow (FF), Sepharose 6 FF<br>MabSelect™, MabSelect Xtra, MabSelect Prisma, MabSelect SuRe™<br>Capto™         | ●<br>●<br>●<br>●<br>●                          | ●<br>●<br>●<br>●<br>●  | ●<br>●<br>●<br>●<br>●  | ●<br>●<br>●<br>●<br>●   |
| <b>Desalting/buffer exchange</b>                          | Sephadex™ Superfine<br>Sephadex Fine, Medium, Coarse  | ●<br>●   | ●<br>●   | ●<br>●   | ●<br>●  |
| <b>Size exclusion chromatography (gel filtration)</b>     | Superdex™ prep grade<br>Sepharose 2B, 4B, 6B, CL-2B, CL-4B, CL-6B<br>Sephacryl™<br>Superose™ prep grade   | ●<br>●<br>●<br>●                               | ●<br>●<br>●<br>●   | ●<br>●<br>●<br>●   | ●<br>●<br>●<br>●  |
| <b>Ion exchange chromatography</b>                        | Sepharose CL-6B<br>Sepharose HP<br>Sepharose 4 FF, Sepharose 6 FF, Sepharose XL<br>Capto<br>Capto ImpRes, Capto S ImpAct<br>SOURCE™ 15<br>SOURCE 30<br>Sephacel™<br>Sephadex A-25, A-50, C-25, C-50 | ●<br>●<br>●<br>●<br>●<br>●<br>●<br>●<br>●<br>● | ●<br>●<br>●<br>●<br>●<br>●<br>●<br>●<br>●<br>●   | ●<br>●<br>●<br>●<br>●<br>●<br>●<br>●<br>●<br>●                           | ●<br>●<br>●<br>●<br>●<br>●<br>●<br>●<br>● <sup>‡</sup><br>●                                 |
| <b>Hydrophobic interaction chromatography</b>             | Sepharose CL-4B<br>SOURCE 15<br>Sepharose HP<br>Sepharose 4 FF, Sepharose 6 FF<br>Capto   | ●<br>●<br>●<br>●<br>●                          | ●<br>●<br>●<br>●<br>●  | ●<br>●<br>●<br>●<br>●  | ●<br>●<br>●<br>●<br>●   |
| <b>Multimodal chromatography</b>                          | Capto<br>Capto ImpRes   | ●<br>●   | ●<br>●   | ●<br>●   | ●<br>●  |

\* See page 3 for more information. Pressure conversion from bar to psi and MPa is shown on page 3.

<sup>†</sup> HiScale columns can be packed on-demand with the resin of your choice — contact your Cytiva representative

<sup>‡</sup> 10 µm net ring should be used

● = recommended    ● = combination is possible, but not recommended    ● = not recommended



## Learn more about column packing!

Watch our instructional column packing videos available on YouTube™

[youtube.com/cytiva](https://www.youtube.com/cytiva)

Download our packing guide

Packing HiScale, XK, and Tricorn chromatography columns with Capto and MabSelect resins



## Make sure that you are using the right chromatography resin.

Download our free Purify App

[cytiva.com/purify](https://www.cytiva.com/purify)



## Focus on your research by letting us pack the column for you!

With over 60 yr of experience in column packing, trust us to pack your column for you

[cytiva.com/custom-column-packing](https://www.cytiva.com/custom-column-packing)

| Column name            | Max. operating pressure |      |     | Column inner diameter (mm) | Approx. min. and max. bed volumes (mL)* | Bed heights min. and max. (mm)* |
|------------------------|-------------------------|------|-----|----------------------------|---|---------------------------------|
|                        | bar                     | psi  | MPa |                            |   |                                 |
| Tricorn 5/20           | 100                     | 1450 | 10  | 5                          | 0.0-0.5                                 | 0-26                            |
| Tricorn 5/50           | 100                     | 1450 | 10  | 5                          | 0.2-1.1                                 | 8-56                            |
| Tricorn 5/100          | 100                     | 1450 | 10  | 5                          | 1.2-2.1                                 | 58-106                          |
| Tricorn 5/150          | 100                     | 1450 | 10  | 5                          | 2.1-3.1                                 | 108-156                         |
| Tricorn 5/200          | 100                     | 1450 | 10  | 5                          | 3.1-4.1                                 | 158-206                         |
| Tricorn 10/20          | 50                      | 725  | 5   | 10                         | 0.0-2.1                                 | 0-26                            |
| Tricorn 10/50          | 50                      | 725  | 5   | 10                         | 0.0-4.4                                 | 0-56                            |
| Tricorn 10/100         | 50                      | 725  | 5   | 10                         | 3.6-8.4                                 | 46-106                          |
| Tricorn 10/150         | 50                      | 725  | 5   | 10                         | 7.6-12.3                                | 96-156                          |
| Tricorn 10/200         | 50                      | 725  | 5   | 10                         | 11.5-16.2                               | 146-206                         |
| Tricorn 10/300         | 50                      | 725  | 5   | 10                         | 19.4-24.1                               | 246-306                         |
| Tricorn 10/600         | 50                      | 725  | 5   | 10                         | 42.9-47.6                               | 546-606                         |
| HiScale 10/40          | 20                      | 290  | 2   | 10                         | 8-31                                    | 100-400                         |
| HiScale 16/20          | 20                      | 290  | 2   | 16                         | 0-40                                    | 0-200                           |
| HiScale 16/40          | 20                      | 290  | 2   | 16                         | 16-80                                   | 80-400                          |
| HiScale 26/20          | 20                      | 290  | 2   | 26                         | 0-106                                   | 0-200                           |
| HiScale 26/40          | 20                      | 290  | 2   | 26                         | 69-212                                  | 130-400                         |
| HiScale 50/20          | 20                      | 290  | 2   | 50                         | 0-393                                   | 0-200                           |
| HiScale 50/40          | 20                      | 290  | 2   | 50                         | 274-785                                 | 140-400                         |
| XK 16/20               | 5                       | 72.5 | 0.5 | 16                         | 0-31                                    | 0-155                           |
| XK 16/40               | 5                       | 72.5 | 0.5 | 16                         | 16-70                                   | 80-350                          |
| XK 16/70               | 5                       | 72.5 | 0.5 | 16                         | 76-130                                  | 380-650                         |
| XK 16/100              | 5                       | 72.5 | 0.5 | 16                         | 136-190                                 | 680-950                         |
| XK 26/20               | 5                       | 72.5 | 0.5 | 26                         | 0-66                                    | 0-125                           |
| XK 26/40               | 5                       | 72.5 | 0.5 | 26                         | 45-186                                  | 85-350                          |
| XK 26/70               | 5                       | 72.5 | 0.5 | 26                         | 204-344                                 | 385-650                         |
| XK 26/100              | 5                       | 72.5 | 0.5 | 26                         | 363-504                                 | 685-950                         |
| XK 50/20               | 3                       | 43.5 | 0.3 | 50                         | 0-274                                   | 0-140                           |
| XK 50/30               | 3                       | 43.5 | 0.3 | 50                         | 0-559                                   | 0-280                           |
| XK 50/60               | 3                       | 43.5 | 0.3 | 50                         | 500-1088                                | 260-560                         |
| XK 50/100              | 3                       | 43.5 | 0.3 | 50                         | 1274-1862                               | 650-950                         |
| C 10/10                | 1                       | 14.5 | 0.1 | 10                         | 0-7                                     | 0-80                            |
| C 10/20                | 1                       | 14.5 | 0.1 | 10                         | 0-14                                    | 0-180                           |
| C 10/40                | 1                       | 14.5 | 0.1 | 10                         | 16-30                                   | 200-380                         |
| C 16/20                | 1                       | 14.5 | 0.1 | 16                         | 0-36                                    | 0-180                           |
| C 16/40                | 1                       | 14.5 | 0.1 | 16                         | 8-77                                    | 40-380                          |
| C 16/70                | 1                       | 14.5 | 0.1 | 16                         | 69-137                                  | 348-680                         |
| C 16/100               | 1                       | 14.5 | 0.1 | 16                         | 129-197                                 | 640-980                         |
| C 26/40                | 1                       | 14.5 | 0.1 | 26                         | 21-202                                  | 40-380                          |
| C 26/70                | 1                       | 14.5 | 0.1 | 26                         | 181-361                                 | 348-680                         |
| C 26/100               | 1                       | 14.5 | 0.1 | 26                         | 340-520                                 | 640-980                         |
| Empty Disposable PD-10 | -                       | -    | -   | -                          | ≤ 13                                    | -                               |

\*The min. values correspond to a packing performed with two adapters.

## cytiva.com

Cytiva and the Drop logo are trademarks of Global Life Sciences IP Holdco LLC or an affiliate. Capto, GraviTrap, HiLoad, HiScale, MabSelect, MabSelect SuRe, Sephacel, Sephacryl, Sephadex, Sepharose, SOURCE, Superdex, Superose and Tricorn are trademarks of Global Life Sciences Solutions USA LLC or an affiliate doing business as Cytiva.

YouTube is a trademark of Google Inc. All other third-party trademarks are the property of their respective owners.

© 2020 Cytiva

All goods and services are sold subject to the terms and conditions of sale of the supplying company operating within the Cytiva business. A copy of those terms and conditions is available on request. Contact your local Cytiva representative for the most current information.

For local office contact information, visit [cytiva.com/contact](https://www.cytiva.com/contact)

CY14026-23Nov20-SG

